

PRODUCT CONFIGURATION OPTIONS

OrderCode:	IED-EP+/DTIVA/E10-Feeder_H/D*****-D*****-Checksum													
Platform: IED-EP+ EuroProt+ platform			Type: DTIVA Overcurrent protections				Configuration: E10-Feeder_H Capacitor protection in 42HP rack size. (Numbers of binary I/O in the standard configuration: 8BOut, 12Bin.)							
Platform specific options	Position	0	1	2	3	4	5	6	7	8	9	10		
	Value	D	*	*	*	*	*	*	*	*	*	*		
Config specific options	Position	0	1	2	3	4	5	6	7	8	9	10	11	12
	Value	D	*	*	*	*	*	*	*	*	*	*	*	*
Checksum	Automatically is created by factory													
Detailed platform specific options														
Platform version													Position 0	
Current version													D	
Power Supply													Position 1	
24V													0	
48V													1	
60V													2	
110V													3	
220/230V													4	
I/O modules													Position 2	
24V													0	
48V													1	
60V													2	
110V													3	
220V													4	
110VAC													5	
230VAC													6	
Mounting methods													Position 3	
Rack													0	
Flush mounting													1	
Wall mounting													2	
Semi-flush													3	
IP54 rated mounting													4	

Wall mounting with terminals	5
No mounting	6
Fold-down mounting	7
Fold-down mounting with terminals	8
CPU first communication port	Position 4
N/A	0
Fiber optical Ethernet MM/ST	1
Fiber optical Ethernet SM/FC	2
PRP/HSR MM/LC	3
Fiber optical Ethernet MM/LC	4
CPU secondary communication port	Position 5
N/A	0
Fiber optical Ethernet MM/ST	1
Fiber optical Ethernet SM/FC	2
RJ-45 Ethernet	3
Serial POF	4
Serial Double ring POF	5
Serial glass fiber	6
RS-485/422	7
Fiber optical Ethernet MM/LC	8
Front panel communication port	Position 6
Ethernet Over Board - EOB	0
RJ-45	1
LCD size	Position 7
N/A	0
3.5	1
5.7	2
IEC61850 protocol (additional charge)	Position 8
No	0
Yes	1
Customization service (additional charge)	Position 9
No	0
Yes	1
Secondary language	Position 10
None	0

HUN	1
GER	2
RUS	3
ITA(N/A)	4
FRA	5
ROU	6
Detailed config specific options	
Configuration version	Position 0
Current version	D
Default binary input module	Position 1
N/A	0
O8	1
O12	2
O16	3
O6R5	4
Default binary output module	Position 2
N/A	0
R4	1
R8	2
R12	3
R16	4
I/O module in position H	Position 3
N/A	0
O8	1
O12	2
O16	3
R4	4
R8	5
R12	6
R16	7
RTD	8
AIC	9
I/O module in position G	Position 4
N/A	0
O8	1

O12	2
O16	3
R4	4
R8	5
R12	6
R16	7
I/O module in position F	Position 5
N/A	0
O8	1
O12	2
O16	3
R4	4
R8	5
R12	6
R16	7
RTD	8
O6R5	9
AIC	A
I/O module in position E	Position 6
N/A	0
O8	1
O12	2
O16	3
R4	4
R8	5
R12	6
R16	7
O9S+BNC	8
O9S+MM/ST	9
ATO	A
AIC	B
I/O module in position B	Position 7
N/A	0
O8	1
O12	2

O16	3
R4	4
R8	5
R12	6
R16	7
RTD	8
AIC	9
Number of NC contacts (R8,R12,R16)	Position 8
0	0
1	1
2	2
4	3
8	4
Trip contacts	Position 9
0	0
2	1
4	2
6	3
8	4
12	5
16	6
Connection type of the capacitor bank	Position 10
Double star	0
Double delta	1
Bridge	2
VT module	Position 11
N/A	0
Measurement	1
Protection	2
Additional CT	Position 12
N/A	0
Measurement	1
Protection	2
Protection (sensitive Io)	3