

### PRODUCT CONFIGURATION OPTIONS

<b>OrderCode:</b>	IED-EP+/DTIVA/E8-Feeder_H/D*****-B*****-Checksum											
<b>Platform:</b> IED-EP+ EuroProt+ platform	<b>Type:</b> DTIVA Overcurrent protections					<b>Configuration:</b> E8-Feeder_H Frequency and over- undervoltage protection in 42HP rack size. (Numbers of binary I/O in the standard configuration: 8BOut, 12Bin.)						
<b>Platform specific options</b>	Position	0	1	2	3	4	5	6	7	8	9	10
	Value	D	*	*	*	*	*	*	*	*	*	*
<b>Config specific options</b>	Position	0	1	2	3	4	5	6	7	8	9	
	Value	B	*	*	*	*	*	*	*	*	*	
<b>Checksum</b>	Automatically is created by factory											
<b>Detailed platform specific options</b>												
<b>Platform version</b>											<b>Position 0</b>	
Current version											D	
<b>Power Supply</b>											<b>Position 1</b>	
24V											0	
48V											1	
60V											2	
110V											3	
220/230V											4	
<b>I/O modules</b>											<b>Position 2</b>	
24V											0	
48V											1	
60V											2	
110V											3	
220V											4	
110VAC											5	
230VAC											6	
<b>Mounting methods</b>											<b>Position 3</b>	
Rack											0	
Flush mounting											1	
Wall mounting											2	
Semi-flush											3	
IP54 rated mounting											4	

Wall mounting with terminals	5
No mounting	6
Fold-down mounting	7
Fold-down mounting with terminals	8
<b>CPU first communication port</b>	<b>Position 4</b>
N/A	0
Fiber optical Ethernet MM/ST	1
Fiber optical Ethernet SM/FC	2
PRP/HSR MM/LC	3
Fiber optical Ethernet MM/LC	4
<b>CPU secondary communication port</b>	<b>Position 5</b>
N/A	0
Fiber optical Ethernet MM/ST	1
Fiber optical Ethernet SM/FC	2
RJ-45 Ethernet	3
Serial POF	4
Serial Double ring POF	5
Serial glass fiber	6
RS-485/422	7
Fiber optical Ethernet MM/LC	8
<b>Front panel communication port</b>	<b>Position 6</b>
Ethernet Over Board - EOB	0
RJ-45	1
<b>LCD size</b>	<b>Position 7</b>
N/A	0
3.5	1
5.7	2
<b>IEC61850 protocol (additional charge)</b>	<b>Position 8</b>
No	0
Yes	1
<b>Customization service (additional charge)</b>	<b>Position 9</b>
No	0
Yes	1
<b>Secondary language</b>	<b>Position 10</b>
None	0

HUN	1
GER	2
RUS	3
ITA(N/A)	4
FRA	5
ROU	6
<b>Detailed config specific options</b>	
<b>Configuration version</b>	<b>Position 0</b>
Current version	B
<b>Default binary input module</b>	<b>Position 1</b>
N/A	0
O8	1
O12	2
O16	3
O6R5	4
<b>Default binary output module</b>	<b>Position 2</b>
N/A	0
R4	1
R8	2
R12	3
R16	4
<b>I/O module in position H</b>	<b>Position 3</b>
N/A	0
O8	1
O12	2
O16	3
R4	4
R8	5
R12	6
R16	7
RTD	8
AIC	9
<b>I/O module in position G</b>	<b>Position 4</b>
N/A	0
O8	1

O12	2
O16	3
R4	4
R8	5
R12	6
R16	7
<b>I/O module in position F</b>	<b>Position 5</b>
N/A	0
O8	1
O12	2
O16	3
R4	4
R8	5
R12	6
R16	7
RTD	8
O6R5	9
AIC	A
<b>I/O module in position E</b>	<b>Position 6</b>
N/A	0
O8	1
O12	2
O16	3
R4	4
R8	5
R12	6
R16	7
O9S+BNC	8
O9S+MM/ST	9
ATO	A
AIC	B
<b>I/O module in position B</b>	<b>Position 7</b>
N/A	0
O8	1
O12	2

O16	3
R4	4
R8	5
R12	6
R16	7
RTD	8
AIC	9
<b>Number of NC contacts (R8,R12,R16)</b>	<b>Position 8</b>
0	0
1	1
2	2
4	3
8	4
<b>Trip contacts</b>	<b>Position 9</b>
0	0
2	1
4	2
6	3
8	4
12	5
16	6