

PRODUCT CONFIGURATION OPTIONS

OrderCode:	IED-EP+ S/S24/Variant 1/C****-D*****-Checksum										
Platform: IED-EP+ S Smart line IED EP+	Type: S24 S24 Smart Line series				Configuration: Variant 1 3Ph+Io overcurrent, motor protection and autorecloser in 24HP industrial enclosure.						
Platform specific options	Position	0	1	2	3	4					
	Value	C	*	*	*	*					
Config specific options	Position	0	1	2	3	4	5	6	7	8	9
	Value	D	*	*	*	*	*	*	*	*	*
Checksum	Automatically is created by factory										
Detailed platform specific options											
Platform version										Position 0	
Current version										C	
Power Supply										Position 1	
24V										0	
48V										1	
60V										2	
110V										3	
220/230V										4	
I/O modules										Position 2	
24V										0	
48V										1	
60V										2	
110V										3	
220V										4	
110VAC										5	
230VAC										6	
Mounting methods										Position 3	
Flush mounting										0	
Din rail mounting										1	
Secondary language										Position 4	
None										0	
HUN										1	
GER										2	

RUS	3
ITA(N/A)	4
FRA	5
ROU	6
Detailed config specific options	
Configuration version	Position 0
Current version	D
Display type	Position 1
B&W	0
3.5" vertical	1
CPU first communication port	Position 2
N/A	0
Fiber optical ethernet MM/ST	1
Fiber optical ethernet SM/FC	2
Fiber optical Ethernet MM/LC	3
CPU secondary communication port	Position 3
N/A	0
Fiber optical Ethernet MM/ST	1
Fiber optical Ethernet SM/FC	2
RJ-45	3
Serial POF	4
Serial glass fiber	5
RS-485/422	6
Fiber optical Ethernet MM/LC	7
I/O module in position D	Position 4
O6R5	0
O8	1
O12	2
R8+00	3
R8+80	4
R8+C0	5
R12+0000	6
R12+4000	7
R12+4400	8
I/O module in position E	Position 5

N/A	0
O8	1
O12	2
R8+00	3
R8+80	4
R8+C0	5
R12+0000	6
R12+4000	7
R12+4400	8
O6R5	9
CT module in position B	Position 6
CT+5151	0
CT+5153(SEF)	1
Capacitor bank protection	Position 7
N/A	0
Yes	1
IEC61850 protocol (additional charge)	Position 8
No	0
Yes	1
Customization service (additional charge)	Position 9
No	0
Yes	1