

### PRODUCT CONFIGURATION OPTIONS

<b>OrderCode:</b>	IED-EP+ S/S24/Variant 4/C****-B*****-Checksum										
<b>Platform:</b> IED-EP+ S Smart line IED EP+	<b>Type:</b> S24 S24 Smart Line series				<b>Configuration:</b> Variant 4 MV line differential protection and autorecloser in 24HP industrial enclosure.						
<b>Platform specific options</b>	Position	0	1	2	3	4					
	Value	C	*	*	*	*					
<b>Config specific options</b>	Position	0	1	2	3	4	5	6	7	8	9
	Value	B	*	*	*	*	*	*	*	*	*
<b>Checksum</b>	Automatically is created by factory										
<b>Detailed platform specific options</b>											
<b>Platform version</b>											<b>Position 0</b>
Current version											C
<b>Power Supply</b>											<b>Position 1</b>
24V											0
48V											1
60V											2
110V											3
220/230V											4
<b>I/O modules</b>											<b>Position 2</b>
24V											0
48V											1
60V											2
110V											3
220V											4
110VAC											5
230VAC											6
<b>Mounting methods</b>											<b>Position 3</b>
Flush mounting											0
Din rail mounting											1
<b>Secondary language</b>											<b>Position 4</b>
None											0
HUN											1
GER											2

RUS	3
ITA(N/A)	4
FRA	5
ROU	6
<b>Detailed config specific options</b>	
<b>Configuration version</b>	<b>Position 0</b>
Current version	B
<b>Display type</b>	<b>Position 1</b>
B&W	0
3.5" vertical	1
<b>CPU first communication port</b>	<b>Position 2</b>
N/A	0
Fiber optical ethernet MM/ST	1
Fiber optical ethernet SM/FC	2
Fiber optical Ethernet MM/LC	3
<b>CPU secondary communication port</b>	<b>Position 3</b>
N/A	0
Fiber optical Ethernet MM/ST	1
Fiber optical Ethernet SM/FC	2
RJ-45	3
Serial POF	4
Serial glass fiber	5
RS-485/422	6
Fiber optical Ethernet MM/LC	7
<b>I/O module in position D</b>	<b>Position 4</b>
O6R5	0
O8	1
O12	2
R8+00	3
R8+80	4
R8+C0	5
R12+0000	6
R12+4000	7
R12+4400	8
<b>I/O module in position E</b>	<b>Position 5</b>

N/A	0
O8	1
O12	2
R8+00	3
R8+80	4
R8+C0	5
R12+0000	6
R12+4000	7
R12+4400	8
O6R5	9
<b>CT module in position B</b>	<b>Position 6</b>
CT+5151	0
CT+5153	1
<b>Type of LD communication</b>	<b>Position 7</b>
Fiber optical SM SH/FC (0-50km)	0
Fiber optical MM/ST (0-2km)	1
<b>IEC61850 protocol (additional charge)</b>	<b>Position 8</b>
No	0
Yes	1
<b>Customization service (additional charge)</b>	<b>Position 9</b>
No	0
Yes	1