

PRODUCT CONFIGURATION OPTIONS

OrderCode:	IED-EP+ S/S24/Variant 6/C****-C*****-Checksum								
Platform: IED-EP+ S Smart line IED EP+	Type: S24 S24 Smart Line series			Configuration: Variant 6 Voltage, frequency protection in 24HP industrial enclosure.					
Platform specific options	Position	0	1	2	3	4			
	Value	C	*	*	*	*			
Config specific options	Position	0	1	2	3	4	5	6	7
	Value	C	*	*	*	*	*	*	*
Checksum	Automatically is created by factory								
Detailed platform specific options									
Platform version									Position 0
Current version									C
Power Supply									Position 1
24V									0
48V									1
60V									2
110V									3
220/230V									4
I/O modules									Position 2
24V									0
48V									1
60V									2
110V									3
220V									4
110VAC									5
230VAC									6
Mounting methods									Position 3
Flush mounting									0
Din rail mounting									1
Secondary language									Position 4
None									0
HUN									1
GER									2

RUS	3
ITA(N/A)	4
FRA	5
ROU	6
Detailed config specific options	
Configuration version	Position 0
Current version	C
Display type	Position 1
B&W	0
3.5" vertical	1
CPU first communication port	Position 2
N/A	0
Fiber optical ethernet MM/ST	1
Fiber optical ethernet SM/FC	2
Fiber optical Ethernet MM/LC	3
CPU secondary communication port	Position 3
N/A	0
Fiber optical Ethernet MM/ST	1
Fiber optical Ethernet SM/FC	2
RJ-45	3
Serial POF	4
Serial glass fiber	5
RS-485/422	6
Fiber optical Ethernet MM/LC	7
I/O module in position D	Position 4
O6R5	0
O8	1
O12	2
R8+00	3
R8+80	4
R8+C0	5
R12+0000	6
R12+4000	7
R12+4400	8
I/O module in position E	Position 5

N/A	0
O8	1
O12	2
R8+00	3
R8+80	4
R8+C0	5
R12+0000	6
R12+4000	7
R12+4400	8
O6R5	9
IEC61850 protocol (additional charge)	Position 6
No	0
Yes	1
Customization service (additional charge)	Position 7
No	0
Yes	1