

PRODUCT CONFIGURATION OPTIONS

OrderCode:	IED-EP+ S/S24/Variant 7/C****-A*****-Checksum									
Platform: IED-EP+ S Smart line IED EP+	Type: S24 S24 Smart Line series			Configuration: Variant 7 High-impedance differential protection in 24HP rack size. (Numbers of binary I/O in the standard configuration: 5BOut, 6BIn.)						
Platform specific options	Position	0	1	2	3	4				
	Value	C	*	*	*	*				
Config specific options	Position	0	1	2	3	4	5	6	7	8
	Value	A	*	*	*	*	*	*	*	*
Checksum	Automatically is created by factory									
Detailed platform specific options										
Platform version										Position 0
Current version										C
Power Supply										Position 1
24V										0
48V										1
60V										2
110V										3
220/230V										4
I/O modules										Position 2
24V										0
48V										1
60V										2
110V										3
220V										4
110VAC										5
230VAC										6
Mounting methods										Position 3
Flush mounting										0
Din rail mounting										1
Secondary language										Position 4
None										0
HUN										1
GER										2

RUS	3
ITA(N/A)	4
FRA	5
ROU	6
Detailed config specific options	
Configuration version	Position 0
Current version	A
Display type	Position 1
B&W	0
3.5" vertical	1
CPU first communication port	Position 2
N/A	0
Fiber optical ethernet MM/ST	1
Fiber optical ethernet SM/FC	2
Fiber optical Ethernet MM/LC	3
CPU secondary communication port	Position 3
N/A	0
Fiber optical Ethernet MM/ST	1
Fiber optical Ethernet SM/FC	2
RJ-45	3
Serial POF	4
Serial glass fiber	5
RS-485/422	6
Fiber optical Ethernet MM/LC	7
I/O module in position D	Position 4
O6R5	0
O8	1
O12	2
R8+00	3
R8+80	4
R8+C0	5
R12+0000	6
R12+4000	7
R12+4400	8
I/O module in position C	Position 5

N/A	0
O8	1
O12	2
R8+00	3
R8+80	4
R8+C0	5
R12+0000	6
R12+4000	7
R12+4400	8
O6R5	9
Number of differential currents	Position 6
1-REF Protection	0
3-BUSBAR Protection	1
IEC61850 protocol (additional charge)	Position 7
No	0
Yes	1
Customization service (additional charge)	Position 8
No	0
Yes	1